



DESCRIPTION

The Phonotech® DK120 element is based on the floating roof principle through its **spring batten** providing a mass-spring-mass effect. Due to its RD120 start and end battens, the Phonotech DK120 system forms an intuitive complete roofing assembly. This decoupling will block any transfer of vibrations through its shock absorbing effect and will provide optimum sound reduction.

INSTALLATION

Due to their light weight, Phonotech elements can be installed by **one person alone**. The intuitive Phonotech attachment system guarantees **easy and fast** assembly.

APPLICATION

The Phonotech® DK120 acoustic system can be laid both on flat **roofing** and **sloped roofing**.

FINISHES

Most of our acoustic systems are tested without a finishing coat (sealing, tiles, etc.) This gives the customer **total freedom** on the choice of roof finish to be applied.

ACCESSORIES

All the accessories needed to assemble the Phonotech DK120 acoustic system (such as retaining profiles, separating tape, acrylic putty, fasteners, etc.) can be supplied on request.

COMPOSITION OF PHONOTECH DK120

1. A spring batten:
 - 20 mm acoustic polyurethane foam
 - A 10 mm coco mat
 - A treated wooden nailer
2. 120 mm specific density stone wool
3. 22 mm waterproof chipboard panel

ACOUSTIC PERFORMANCES

The Phonotech DK acoustic system guarantees **highly efficient sound insulation** relying on extensive laboratory testing subsequently confirmed by **on-site measurements**.

The Phonotech panel's acoustic performances, depending on implementation on different supports (TAB106, perforated sheets, wood, etc.), are given on the system sheets.

Dimensions (mm)			Thermal resistance (m ² .K/W)	Weight (item)	Weight (kg/m ²)
Length	Width	Thickness			
1200	600	142	3,55	17,81	24,73

ADDRESS

Zoning Industriel les Plénesses
Rue des Waides 8, 4890 Thimister
Belgium

WEBSITE

www.phonotech.com

EMAIL

info@phonotech.com

PHONE

+32 (0) 87 33 33 30

FAX

+32 (0) 87 78 52 30